

HD-1000

HANDHELD OIL IN WATER ANALYZER



Fluorescence



Spectroscopy

The Advanced Sensors HD-1000 is a portable handheld Oil in Water analyzer with an integrated probe to measure oil directly in water samples. The industrial flexible probe allows for real-time measurements, with spectral analysis which enables oil type identification. These features make the HD-1000 a unique and revolutionary device for the Oil in Water analysis industry.

FEATURES

- Real-time measurement
- Accommodates both direct Oil in Water measurement and solvent extraction measurement
- Laser Induced Fluorescence (LIF)
- Various measurement ranges configurable (0-10ppm, 0-100ppm [...] up to 0-3,000ppm)
- Integrated spectral analysis
- Robust, flexible optical probe for ease of measurement in various applications
- Incorporated touch screen with auto orientation
- On screen notepad
- On screen user manual
- Bluetooth and Wi-Fi communications
- Portable and light weight (0.8kg)
- User interface available in English, with some key phrases available in Arabic, French, Norwegian, Italian, Chinese and Spanish.

BENEFITS

- Easy to use
- No solvents or consumables required
- Instantaneous measurement: no sample pretreatment or preparation required
- Spectral analysis allows oil recognition and the presence of chemicals
- Automatic software update (optional)
- Measurement data log can be shared via email, Bluetooth or Wi-Fi
- Downloadable oil calibration files from cloud based library



Measurement Performance	
Measurement principle	Laser Induced Fluorescence (LIF)
Range	0-3,000ppm
Repeatability	±1% of measurement range, matrix dependent
Response time	±1% of full scale range
Operating Conditions	
Operational ambient temperature	-5°C to +50°C
Spectral Analysis Specification	
Emission wavelength range	400-1,100nm
Resolution	0.5nm
Utilities	
Power	Rechargeable battery (3,000 mAh) 5Vdc (Charging device required: input 100-240VAC, Output 2A)
Material	
Enclosure material	Aluminium
Weight & Dimensions (for shipping)	
Weight	0.8kg
Dimensions	85W x 152D x 52H mm
Flexible probe length	1.2m
Communications	
Wireless (Wi-Fi)	Standard
Bluetooth	Standard
Internal data storage	9GB
Security	Password protection
Certification	
Certification	CE Compliant