





# Portable Combustion & Emissions Analyzer PCA® 400

FEATURES	BENEFITS
Large touch screen display	Flexible, intuitive operation
Bluetooth <sup>®</sup> wireless communications	Quickly and easily stream data to smartphones & tablets
Long-life O₂ sensor (5 Year Warranty)	Reduces maintenance cost and downtime
Customizable reports for data viewing	Easy compliance reporting and record keeping
Standard Li-Ion Battery	Operates > 12 hours; optional AA batteries or AC power
Rugged, one step probe connection	Easy to attach; exceptional durability
Automatic Sensor Protection	Protects sensors in the toughest combustion environments, extending life
B-Smart Sensor Exchange Program	Delivers pre-calibrated sensors to your door to eliminate field calibration and minimizes maintenance

# DESCRIPTION

Bacharach's new PCA 400 can measure up to 4 gases at once with 6 sensor options.

Users have the option to save measured data in the unit as discreet tests or stream it live via Bluetooth<sup>®</sup> communications or other smart hand-held device for longer test protocol.

Reports are easily and quickly generated to satisfy compliance requirements. Interchangeable power options (rechargeable Li-Ion, 'AA' alkalines or line power) ensure the unit is always ready for use.

Probes and hoses come in a variety of lengths and materials to satisfy a wide range of measurement and application requirements.

Automatic sensor protection not only guards the sensors from damage, but doubles their measurement range under high load conditions for increased flexibility.



#### HOW TO CONTACT US:

Bacharach US Customer Service: +1 724 334 5000 Bacharach EU Customer Service: +353 1 284 6388 www.mybacharach.com

PCA<sup>®</sup> is a trademark of Bacharach, Inc.

# mybacharach.com

For more information about the PCA 400 and other Bacharach products scan here.





INDUSTRIAL

### **ORDERING INFORMATION**

P/NDESCRIPTION2411-1112PCA 400 w/ O₂, CO, NO, 12 in. probe with 7.5 ft. STD tubing, standard case and Bluetooth® printer2412-1312PCA 400 w/ O₂, CO, NO, NO₂, 12 in. probe with 7.5 ft. VITON™ tubing, standard case and Bluetooth® printer2413-1312PCA 400 w/ O₂, CO, NO, SO₂, 12 in. probe with 7.5 ft. VITON™ tubing, standard case and Bluetooth® printer

## SPECIFICATIONS

MEASUREMENTS:	DESCRIPTION
02	0 to 29%
CO-H <sub>2</sub> compensated	0 to 10,000 ppm
CO (high range)	0 to 40,000 ppm
NO	0 to 3,000 ppm
NO <sub>2</sub>	0 to 500 ppm
SO <sub>2</sub>	0 to 5,000 ppm
Size (L x W x D, approx.)	10" x 3.8" x 2.5" (25.4 x 9.7 x 6.4 cm)
Weight (approx.)	1.5 lbs (0.68 kg) w/Li-lon battery pack
Power	Three options: Rechargable Li-Ion battery, 4x AA or wall adapter (5V USB)
Display	4.3 in. (10.9 cm) color touch panel LCD
Run Time	12 to 14 hours (typical, w/included Li-lon battery pack)
Warm-up Time	60 seconds
Fuels <sup>[1]</sup>	Natural gas, coal, oil 2/4/6, propane, wood/biofuels, kerosene, bagasse, digester
	gas, B5, pellets, KOKS, LEG, LPG, butane, wood chips
Operating Conditions	Temperature: 32 to 113° F (0 to 45° C)
	Humidity: 5 to 90% RH non-condensing
	Air Pressure: 1 atmosphere ±10%
	Position: Any
Environmental Conditions	Stack Temperature: -4 to 2192°F (-20 to 1200 °C)
	Ambient Temperature: -4 to 999 °F (-20 to 537 °C)
	Draft/Differential Pressure: $\pm$ 72 inch of H <sub>2</sub> O ( $\pm$ 179mB)
Memory	500 sets of records
Communications	Bluetooth <sup>®</sup> 4.0, USB 2.0 (micro-B), IrDA
Approvals	CE Mark pending
Warranty	2 years for instrument, 5 years for $O_2$ sensor

<sup>[1]</sup> Depending upon combustion equation setting (North American or Siegert) - see manual for details.

## **ACCESSORIES AND OPTIONS:**

A variety of probe and tubing options are available to customize your instrument for your application.



Optional sample conditioner effectively removes water and particulates from flue gas in high heat emissions applications.





Pittsburgh, PA, USA | Dublin, IRE | Gloucester, UK | Stanardsville, VA, USA | Toronto, CAN mybacharach.com | help@mybacharach.com

BACHARACH