



ToxiRAE Pro CO₂

Personal Wireless Monitor for Carbon Dioxide

The ToxiRAE Pro CO₂ is the world's first wireless personal carbon dioxide monitor. It provides safety professionals with wireless remote access to real-time instrument readings and alarm status for better visibility and faster incident response. The ToxiRAE Pro offers datalogging capability and is equipped with a "Man Down" alarm and policy enforcement to ensure greater safety while making sure compliance-related procedures such as periodic testing and calibration are performed.

- Wireless remote monitoring enhances worker safety
- Man Down Alarm with real-time wireless remote notification
- Easy to maintain, with replaceable sensor, filter, and Li-Ion battery
- Fully automatic bump testing and calibration with AutoRAE 2

Applications

- Chemical manufacturing
- Food and beverage
- Wineries and breweries
- Landfills
- Water and wastewater facilities

Optional Accessories

- AutoRAE 2 Automatic Test and Calibration System
- Multi-unit charging station for up to five monitors



AutoRAE 2 with ToxiRAE Pro cradles



ToxiRAE Pro CO₂ comes with:

- ToxiRAE Pro CO₂ monitor with sensor as specified, alligator clip, protective rubber boot, and rechargeable battery installed
- Charging and PC communication cradle
- PC communication cable
- AC adapter (100 to 240 V, 50/60 Hz AC to 12 V DC)
- Calibration adapters
- Quick Start Guide
- CD with documentation
- Calibration card, quality certificate, and warranty/registration card

FEATURES & BENEFITS

- Wireless access to real-time instrument readings and alarm status from any location
- Unmistakable five-way local and remote wireless notification of alarm conditions
- Intelligent sensor stores calibration data, so it can be swapped in the field
- Largest display in its class
- Continuous datalogging
- Easy to use
- Reliable and rugged
- Device Management with Honeywell SafetySuite

ToxiRAE Pro CO₂ Specifications

| SPECIFICATIONS | |
|-------------------------------------|---|
| SIZE | 4.6" H x 2.4" W x 1.2" D (118 x 60 x 30 mm) |
| WEIGHT | 7.76 oz. (220 g) |
| SENSORS | Nondispersive infrared sensor Range: 0 to 50,000 ppm Resolution: 100 ppm |
| BATTERY | Rechargeable Li-ion battery - Operating time: > 11 hours (normal operation 25° C / 77° F, non-wireless) - Recharge time: < 4 hours through charging cradle |
| DISPLAY | Graphical LCD display with white LED backlighting (activated when monitor is in alarm or with a button press) |
| DISPLAY READOUT | - Real-time reading of gas concentrations in parts per million (ppm); battery status; datalogging on/off; wireless on/off, and reception quality - STEL, TWA, and peak values |
| KEYPAD | 2 buttons for operation and programming |
| SAMPLING | Diffusion |
| CALIBRATION | Automatic with AutoRAE 2 Test and Calibration System or manual |
| ALARM MODES | - Wireless remote alarm notification; audible (95 dB @ 30 cm), vibration, visible alarm (ashing bright red LEDs), and on-screen indication of alarm conditions. - Man Down Alarm with pre-alarm and real-time remote wireless notification |
| DATALOGGING | - Continuous datalogging with a three-month capacity (at one-minute intervals) - User-configurable datalogging interval (from 1 to 3,600 seconds) |
| COMMUNICATION AND DATA DOWNLOAD | - Data download and instrument setup on PC via charging and PC comm. cradle - Data download via AutoRAE 2 Automatic Test and Calibration System - Wireless data and status transmission ¹ via built-in RF modem (optional) |
| WIRELESS NETWORK | ProRAE Guardian Real-Time Wireless Safety System or Closed-Loop Network with the EchoView Host |
| WIRELESS FREQUENCY | ISM license-free bands |
| WIRELESS RANGE (TYPICAL) | ToxiRAE Pro to Mesh Router or EchoView Host ~ 660 feet (200 meters) ToxiRAE Pro to RAELink3 Mesh or RAELink3 Z1 Mesh modems ~ 330 feet (100 meters) |
| OPERATING TEMPERATURE | -4° to 131° F (-20° to 55° C) |
| HUMIDITY | 0% to 95% relative humidity (non-condensing) |
| DUST AND WATER RESISTANCE | IP-65 |
| HAZARDOUS LOCATION APPROVALS | Unit cannot be used in hazardous area |
| CE COMPLIANCE (EUROPEAN CONFORMITY) | EMC directive: 2004/108/EC. R&TTE directive: 1999/5/EC |
| WARRANTY | - Two years on non-consumable components - One year on all other sensors, battery, and other consumable parts |

ORDERING INFORMATION (MODEL: PGM-1850)

- Wireless or non-wireless versions are available¹
- Contact your local Honeywell RAE Systems distributor for part numbers for monitors, accessories, maintenance kits, gas, sensors, and replacement parts

1. Wireless units have a functioning RF modem and are ready for wireless deployments. Non-wireless units cannot be upgraded to wireless. Additional equipment and/or software licenses may be required to enable remote wireless monitoring and alarm transmission.

Specifications are subject to change.

For more information

www.honeywellanalytics.com
www.raesystems.com

Europe, Middle East, Africa

Life Safety Distribution GmbH
Tel: 00800 333 222 44 (Freephone number)
Tel: +41 44 943 4380 (Alternative number)
Middle East Tel: +971 4 450 5800 (Fixed Gas Detection)
gasdetection@honeywell.com

Americas

Honeywell Analytics Distribution Inc.
Tel: +1 847 955 8200
Toll free: +1 800 538 0363
detectgas@honeywell.com
Honeywell RAE Systems
Phone: +1 408 952 8200
Toll Free: +1 888 723 4800

Asia Pacific

Honeywell Analytics Asia Pacific
Tel: +82 (0) 2 6909 0300
India Tel: +91 124 4752700
China Tel: +86 10 5885 8788-3000
analytics.ap@honeywell.com

Technical Services

EMEA: HAexpert@honeywell.com
US: ha.us.service@honeywell.com
AP: ha.ap.service@honeywell.com

Device Management with
Honeywell SafetySuite



honeywellanalytics.com/SafetySuite

Datasheet_ToxiRAE Pro CO2_DS-1085-04_EMEA-EN
05/18 ©2018 Honeywell International Inc.

Honeywell